


ELECTRICAL SYMBOLS - POWER PLAN



DISTRIBUTION PANEL



PANELBOARD, FLUSH MOUNTED



PANELBOARD, SURFACE MOUNTED



RECEPTACLE, CLOCK HANGER



RECEPTACLE, DUPLEX



RECEPTACLE, DUPLEX ON EMERGENCY POWER



RECEPTACLE, DUPLEX WITH GROUND FAULT CIRCUIT INTERRUPT



RECEPTACLE, QUADRAPLEX



RECEPTACLE, SINGLE



RECEPTACLE, SINGLE WITH SWITCH



RECEPTACLE, SPECIAL PURPOSE

A = 120V, 20A, 1 PHASE, 2-POLE, 3W, NEMA 5-20P

B = 208V, 20A, 1 PHASE, 2-POLE, 3W, NEMA 6-20P

C = 120V, 30A, 1 PHASE, 2-POLE, 3W, NEMA 5-30P

D = 208V, 30A, 1 PHASE, 2-POLE, 3W, NEMA 6-30P

E = 208V, 60A, 1 PHASE, 3-POLE, 4W, NEMA 14-60P

F = 208V, 30A, 3 PHASE, 3-POLE 4W, NEMA 15-30P

G = 208V, 50A, 3 PHASE, 3 POLE, 4W, NEMA 15-30P

H = 208V, 60A, 3 PHASE, 3 POLE, 4W, NEMA 15-60P



RECEPTACLE, SWITCHED DUPLEX



DROP CORD, SINGLE CONVENIENCE OUTLET, 3-WIRE, (C 20A, W/#12 CONDUCTORS IN FLEXIBLE CORD (CENTER TO CENTER) 6'-6" [1981mm] AFF. MINIMUM).



ELECTRICAL STRIP MOLD (OUTLETS ON 2'-0" [610mm] DESIGNATED ON DRAWINGS), MTD 3'-6" [1067mm] AFF. INDICATED.



DISCONNECT SWITCH, FUSED



DISCONNECT SWITCH, UNFUSED



STARTER, COMBINATION WITH DISCONNECT SWITCH

VA



U.S. Department
of Veterans Affairs

DETAIL TITLE / ELECTRICAL SYMBOLS-POWER PLAN

SCALE: NONE

DATE ISSUED: JULY 1, 2020

CAD DETAIL NO.:

SD260511-10.DWG